

SPECIFICATION FOR DRIZIT® ACTIVE 240GSM ANTI STATIC OIL ROLLS



	MRA24MD001BG	LRA24MD001BG
Size	50cm x 45m	100cm x 45m
Perforations	n/a	n/a
Colour	White	White
Pack Quantity	1	1
Pack Wt (gross)	5.4 kg	10.8 kg
Pack Size	50 x 34 x 34 cm	100 x 34 x 34 cm
Sorbency (pack)	93 - 124 litres	187 - 249 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

- Composition:** >99.5% Polypropylene, <0.5% antistatic additive
Meltblown, ultrasonically bonded
- Basis Wt:** 240gsm
- Pack Type:** Bag
- Compatibility:** Water-repellency exceeds requirements of BS 7959-2:2000.
May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc.
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
- Fire Resistance:** Good. (Physically flame-retardant)
Incinerable to zero ash.
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
- Safety Data:** Refer to our Safety Data Sheet.
This product is non-toxic to users and to aquatic life.
Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018