

SPECIFICATION FOR DRIZIT® ACTIVE OIL ONLY BILGE BOOMS



	0112/0.5/RING/ROPE
Size	20cm dia x 50cm
Colour	Grey boom Blue rope
Pack Quantity	10
Pack Wt (gross)	10.9 kg
Sorbency (pack)	130 - 143 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

- Outer Casing:** 100% polypropylene spun-bonded
Tensile strength (mean): 400N (200mm strip/EN ISO 10319)
High UV resistance
- Filler:** Polypropylene or other fibres
- Fitted with:** Ring either end of boom for joining
3m of 6mm UV stabilized polypropylene rope
- Pack Type:** Bag
- Compatibility:** Water-repellency exceeds requirements of BS 7959-2:2000.
May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc.
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
- Fire Resistance:** Good. (Physically flame-retardant)
Incinerable to low ash.
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
- Safety Data:** Refer to our Safety Data Sheet.
This product is non-toxic to users and to aquatic life.
Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018