

## SPECIFICATION FOR DRIZIT<sup>®</sup> ACTIVE OIL ONLY BOOMS



	0112/1.5	0112/3	0112/4
<b>Size</b>	20cm dia x 1.5m	20cm dia x 3m	20cm dia x 4m
<b>Colour</b>	Grey	Grey	Grey
<b>Pack Quantity</b>	4	2	2
<b>Pack Wt (gross)</b>	12.6 kg	12.5 kg	16.5 kg
<b>Pack Size</b>	60 x 35 x 95 cm	70 x 55 x 40 cm	65 x 40 x 90 cm
<b>Sorbency (pack)</b>	157 - 172 litres	157 - 172 litres	210 - 230 litres

*Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain*

- Outer Casing:** Nonwoven based on thermally bonded continuous bi-component filaments.  
PET core and PA-6 skin, 10 dtex per filament.  
Tensile strength: 280N (5mm strip/EN ISO 10319).  
High UV resistance.
- Filler:** Polypropylene or other fibres.
- Fitted with:** 6mm UV stabilized polypropylene rope along length, with 100cm tails for fixing.  
Polypropylene webbing tapes for positive close joint.
- Pack Type:** Bag
- Compatibility:** Water-repellency exceeds requirements of BS 7959-2:2000.  
May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc.  
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
- Fire Resistance:** Good. (Physically flame-retardant)  
Incinerable to zero ash.
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
- Safety Data:** Refer to our Safety Data Sheet.  
This product is non-toxic to users and to aquatic life.  
Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018