

SPECIFICATION FOR DRIZIT® ANTI STATIC OIL SOCKS



	0130/125/10/A	0130/125/20/A	0130/125/40/A
Size	7.5cm dia x 1.25m	7.5cm dia x 1.25m	7.5cm dia x 1.25m
Colour	White	White	White
Pack Quantity	10	20	40
Pack Wt (gross)	3.1 kg	6.2 kg	12.2 kg
Pack Size	40 x 53 x 24 cm	50 x 45 x 40 cm	65 x 45 x 80 cm
Sorbency (pack)	35 - 40 litres	70 - 80 litres	140 - 160 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

- Outer Casing:** 100% polypropylene spun-bonded, Static Dissipating
Tensile strength (mean): 400N (200mm strip/EN ISO 10319)
UV resistant
- Filler:** Polypropylene and other fibres
- Fitted With:** Polypropylene thread tails for joining
- Pack Type:** Bag
- Compatibility:** Water-repellency exceeds requirements of BS 7959-2:2000.
May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc.
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
- Fire Resistance:** Good. (Physically flame-retardant)
Incinerable to zero ash.
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
- Safety Data:** Refer to our Safety Data Sheet.
This product is non-toxic to users and to aquatic life.
Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018