

SPECIFICATION FOR DRIZIT® MAINTENANCE SOCKS

	0330/125/10	0330/125/20	0330/125/40	0330/300/5	0330/600/4
Size	7.5cm dia x 1.25m	7.5cm dia x 1.25m	7.5cm dia x 1.25m	7.5cm dia x 3m	7.5cm dia x 6m
Colour	Grey	Grey	Grey	Grey	Grey
Pack Quantity	10	20	40	5	4
Pack Wt (gross)	3.3 kg	5.4 kg	10.8 kg	4.1 kg	6.5 kg
Pack Size	50 x 35 x 18 cm	50 x 45 x 40 cm	85 x 45 x 45 cm	30 x 47 x 47 cm	50 x 50 x 50 cm
Sorbency (pack)	25 - 36 litres	50 - 72 litres	100 - 144 litres	30 - 42 litres	48 - 60 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using water. Higher figure based on high viscosity liquid with no drain



- Outer Casing:** 100% polypropylene spun-bonded
Tensile strength (mean): 400N (200mm strip/EN ISO 10319)
UV resistant
- Filler:** Natural and/or synthetic fibre
- Fitted With:** Polypropylene thread tails for joining
- Pack Type:** Bag

Compatibility: May be safely used with all aqueous solutions and liquids immiscible with water, such as hydrocarbons, solvents, mineral oils, **with the exception of strong oxidising agents.** Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.

Fire Resistance: Good. (Physically flame-retardant)
Incinerable to zero ash.

Disposal: Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.

Safety Data: Refer to our Safety Data Sheet.
This product is non-toxic to users and to aquatic life.
Further technical advice is available if required.

Note: All weights, dimensions, and other figures quoted are approximate.

Revision Date: 24/02/2020