

SPECIFICATION FOR DRIZIT® OIL ANTISTATIC SPILL KIT 50



	0170/AS/SK50
Container Size	54 x 14 x 48 cm
Container Volume	50 litres
Container Colour	Yellow
Pack Wt (gross)	3.7 kg
Sorbency	45 – 54 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

Container: UV stabilised waterproof polyester bag

Contents:

- 25 Oil Antistatic Pads
- 4 Oil Socks 125 x 7.5 cm
- 1 Oil Cushion
- 2 Disposal bags and ties

Instructions for use: It is important that a suitable and sufficient Risk Assessment is carried out on each incident and correct PPE is worn.
Depending on the nature of the spill a combination of the contents of the kit may be used.

Compatibility: The absorbents within this kit may be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils.
Water-repellency exceeds requirements of BS 7959-2:2000.
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.

Disposal: Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.

Safety Data: Further technical advice is available if required.

Note: All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018