

## SPECIFICATION FOR DRIZIT® SKIRTED OIL ONLY BOOMS



	0112/3/S
<b>Size</b>	15cm dia x 3m, 20cm skirt
<b>Colour</b>	Grey
<b>Pack Quantity</b>	2
<b>Pack Wt (gross)</b>	14.8 kg
<b>Pack Size</b>	70 x 55 x 40 cm
<b>Sorbency (pack)</b>	70 - 92 litres

*Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain*

**Outer Casing:** Nonwoven based on thermally bonded continuous bi-component filaments, PET core and PA-6 skin, 10 dtex per filament. Tensile strength: 280N (5mm strip/EN ISO 10319). High UV resistance.

**Skirt:** Black PE tube (250 microns), with chain for ballast, eyelet to locate joining ropes, and solid mass adhesive strip for joining

**Filler:** Polypropylene or other fibres.

**Fitted with:** 6mm UV stabilized polypropylene rope along length, with 100cm tails for fixing, and 0.5m tails for joining.

**Pack Type:** Bag

**Compatibility:** Water-repellency exceeds requirements of BS 7959-2:2000. May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc. Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.

**Fire Resistance:** Good. (Physically flame-retardant)  
Incinerable to low ash.

**Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.

**Safety Data:** Refer to our Safety Data Sheet.  
This product is non-toxic to users and to aquatic life.  
Further technical advice is available if required.

**Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018