

## SPECIFICATION FOR DRIZIT® ULTRA HEAVY DUTY OIL ONLY BOOMS



	0112/3/HD	0112/4/HD
<b>Size</b>	20cm dia x 3m	20cm dia x 4m
<b>Colour</b>	Green	Green
<b>Pack Quantity</b>	2	2
<b>Pack Wt (gross)</b>	12.4 kg	16.4 kg
<b>Pack Size</b>	70 x 55 x 40 cm	65 x 40 x 90 cm
<b>Sorbency (pack)</b>	157 - 172 litres	210 - 230 litres

*Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain*

- Outer Casing:** 100% polypropylene, UV stabilized.  
Tensile strength 600N/5cm (weft), 1400N/5cm (warp).
- Filler:** Polypropylene or other fibres.
- Fitted with:** 6mm UV stabilized polypropylene rope integral to seam, with 100cm tails for fixing.  
Ring/carbine hook system for positive close joint. (Zinc-plated steel)  
Spare disposal bag included in pack.
- Pack Type:** Bag
- Compatibility:** Water-repellency exceeds requirements of BS 7959-2:2000.  
May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc.  
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
- Fire Resistance:** Good. (Physically flame-retardant)  
Incinerable to minimum ash.
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
- Safety Data:** Refer to our Safety Data Sheet.  
This product is non-toxic to users and to aquatic life.  
Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018