

SPECIFICATION FOR ECONOMY BUNDED STORES



	1840/SMC21	1840/SMC31	1840/SMC41
Size	235 x 216 x 224.7 cm	308 x 216 x 224.7 cm	408 x 216 x 224.7 cm
Sump Capacity	680 litres	904 litres	1212 litres
Weight	449 kg	556 kg	696 kg

Construction: Chassis, including sumped base
 Floor grate
 Side wall panels
 Roof panel
 Double-door panels featuring the newly improved double locking system
 Fastening elements
 Numerous optional extras, including Forklift and adjustable levelling feet.

Floor: Sumped chassis base, with suspended floor grate.

Walls & Roof Panels: 0.50mm box profile galvanized steel panels.
 The panels are strengthened with spot welded galvanized steel frame sections at the edges of each panel.
 The roof section has two integral gutters for effective rainwater dispersal to all four corners of the container.

Door Panels: 0.50mm box profile galvanized steel panel, with powder coated finish.
 The 2 door panels are produced by a spot welding process.
 The doors are mounted into the frame with galvanized hinges.
 Complete with two 64mm Euro deadlocks with replaceable cylinders & a central roller catch.
 Double-Door width: 1900mm, hinged on the right and left, outward opening.

Fastening Elements: Four 12 mm diameter rods are used to connect the roof to the chassis.
 These also form lifting eyes for use with a crane.
 Additional roof security bolts are supplied to prevent external access.

Powder Coating: The doors are powder coated in RAL3000.

Note: All weights, dimensions, and other figures quoted are approximate.

Revision Date: 07/11/2018