

SPECIFICATION FOR FRAME TANKS



	0414/0400/PVC	0414/0800/PVC	0414/2000/PVC	0414/4000/PVC
Capacity	400 litres	800 litres	2000 litres	4000 litres
Size	100 x 100 x 40cm	200 x 100 x 40cm	100 x 200 x 100cm	200 x 200 x 100cm
Colour	Yellow	Yellow	Yellow	Yellow

Description: A portable self-assembly tank for containment and temporary storage of oil and contaminated water

Construction: 900 gsm PVC-coated material, RF welded.
Also available in PU upon request.

Frame: Constructed from black, powder coated mild steel.
Legs: 50 x 50 x 2.5mm
Top rails: 25 x 25 x 2mm
Base plates: 150 dia. x 5mm
Top rail connectors: 20mm bright bars
All connecting bolts: stainless steel

Instructions for use: The following recommendations must be observed to ensure safe use of the Frame Tank and to minimise damage:
Ensure that ground surface on which the Frame Tank is to be placed is free of sharp objects.
Regularly inspect the Frame Tank for signs of damage.

Compatibility: Suitable for short term contact/storage of oil or oil-contaminated water.
For other applications please consult our technical department.

Safety Data: If contaminated wash thoroughly before returning to store or re-using the Frame Tank.
Further technical advice is available if required.

Note: All weights, dimensions, and other figures quoted are approximate.

Revision Date: 07/11/2018