

SPECIFICATION FOR TRIBUND TANKS



	0416/
Capacity available	270 – 30,000 litres
Size	Varies dependant on capacity
Height	30 cm
Colour	Yellow

- Description:** A portable bund for containment and temporary storage of oil and contaminated water.
- Construction:** 900 gsm PVC-coated material, RF welded.
- Fitted with:** Corner support struts and side support struts
Ground sheet available (at additional cost)
- Properties:** Tensile strength of material = 4000/3500 N per 50 mm strip (BS3424/6B)
Tear strength of material = 1000/800 N (BS3424/7B)
Coating Adhesion = 90 N/50mm (BS3424/9B)
UV resistance: good
- Instructions for use:** The following recommendations must be observed to ensure safe use of the Tribund and to minimise damage:
Ensure that ground surface on which the Tribund is to be placed is free of sharp objects.
Unfold the Tribund and place in position; pull up the sides making sure that all the support struts are erected.
Take care when moving drums, machines etc in and out of the Tribund: if necessary pull down the sides to avoid damage to the sides and the support struts
Regularly inspect the Tribund for signs of damage
If left outside for protracted periods ensure that any rainwater build-up is removed regularly as this will affect the bund capacity
- Compatibility:** Suitable for short term contact/storage of oil or oil-contaminated water.
For other applications please consult our technical department.
- Safety Data:** If contaminated wash thoroughly before returning to store or re-installing the Tribund.
Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 07/11/2018