

Product Technical Specification

Clearspray 100D2F



Product Summary

The CLEARSPRAY 100D2F is an ABS Design Approved electric dispersant pump unit for the application of Neat (Concentrated) or Diluted oil dispersant from Tugs, Offshore Support Vessels and other specialised Craft. It features an electric below deck Pump Unit with Direct On-Line Starter, Bridge On/Off Control Panel, Dilute and Outlet Flow Meters and Spraying Equipment such as Spray Arms, AFEDO™ Nozzles or Hand Lances. The Spraying Equipment is described in separate Technical Specifications.

Options Available

1. Pump Spares Kit

2. Personal Protective Equipment (PPE)

3. UK Approved Dispersant

4. Spray Arm, AFEDO and Hand Lance Spraying Equipment

Shipping Specification

Supplied in Case 127cm x 72cm x 74cm

Gross Wt 246kg

More Info

Documentation Operating Manuals

System Wiring Diagram

Quality Control Manufactured under a

BS EN ISO 9001 Quality System

Pump Unit

Motive Unit: IP 55, 3 Ph ,1.1 kW Electric Motor

for below deck mounting

Pump: Roller Type Positive Displacement

Pump, 1000 LPM @ 4 bar

Pipework: Gunmetal and Stainless Steel **Eductor:** Proportioning Type (0 - 25%)

Flow Meter: Dispersant Flow Meter

Outlet Flow Meter

Base Plate: Painted Mild Steel
Valves (Manual): Flow Control Valve

Dispersant Control Valve


Eductor Shut-Off Valve

Control: Motor Direct On-Line Starter with

Bridge On/Off Control Panel

Pressure Relief Valve: 0 to 10 Bar setting.

Pressure Gauge: Dual Scale



email sales@darcy.co.ukcall 0800 0370 899



