



SPECIFICATION FOR DRIZIT® EXTREME 300GSM OIL ONLY PADS (WHITE)



	PDW30SL100BG
Size	40cm x 50cm
Perforations	n/a
Colour	White
Pack Quantity	100
Pack Wt (gross)	6.0 kg
Pack Size	50 x 40 x 33 cm
Sorbency (pack)	97 - 125 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

Composition: 100% Polypropylene

Meltblown, ultrasonically bonded, spunbond laminated on one side

Basis Wt: 17gsm spunbond 283gsm meltblown

Pack Type: Bag

Compatibility: Water-repellency exceeds requirements of BS 7959-2:2000.

May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents,

mineral oils etc.

Before any use in a spill situation a proper risk assessment should be carried out and all

hazardous properties of the liquid or dangerous reactions taken into account.

Fire Resistance: Good. (Physically flame-retardant)

Incinerable to zero ash.

Disposal: Used sorbents may be disposed of by landfill or incineration, in accordance with local and

national regulations, taking into account the classification of the liquid absorbed.

Safety Data: Refer to our Safety Data Sheet.

This product is non-toxic to users and to aquatic life.

Further technical advice is available if required.

Note: All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018



