



## SPECIFICATION FOR DRIZIT® OIL BARREL SPILL KIT

Nuc or United States		0170/DSK/70
	Container Size	40 diameter x 62 cm
	Container Volume	60 litres
	Container Colour	Blue
	Pack Wt (gross)	5.7 kg
	Sorbency	79 - 96 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

**Container:** PE open top barrel with side handles and snap ring lid.

Contents: 50 Oil Pads

2 Oil Cushions

4 Oil Socks 125 x 7.5 cm1 Dammit® X Ready Mix Slab

1 Disposal Bag and Tie

**Replenishment:** A full refill kit is available for this product. Please use code 0170/DSK/70/R.

To order further kits, refill sets or packs of individual items please contact us.

Instructions for use: It is important that a suitable and sufficient Risk Assessment is carried out on each incident

and correct PPE is worn.

Depending on the nature of the spill a combination of the contents of the kit may be used.

Compatibility: The absorbents within this kit may be safely used with all liquids immiscible with water, such

as hydrocarbons, solvents, mineral oils.

Water-repellency exceeds requirements of BS 7959-2:2000.

Before any use in a spill situation a proper risk assessment should be carried out and all

hazardous properties of the liquid or dangerous reactions taken into account.

Disposal: Used sorbents may be disposed of by landfill or incineration, in accordance with local and

national regulations, taking into account the classification of the liquid absorbed.

**Safety Data:** Further technical advice is available if required.

**Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 22/10/2024



