

## SPECIFICATION FOR DRIZIT® OIL ONLY SOCKS (BLUE)

	0130/125/10	0130/125/20	0130/125/40	0130/300/5	0130/600/4
<b>Size</b>	7.5cm dia x 1.25m	7.5cm dia x 1.25m	7.5cm dia x 1.25m	7.5cm dia x 3m	7.5cm dia x 6m
<b>Colour</b>	Blue	Blue	Blue	Blue	Blue
<b>Pack Quantity</b>	10	20	40	5	4
<b>Pack Wt (gross)</b>	3.1 kg	6.2 kg	12.2 kg	3.9 kg	6.0 kg
<b>Pack Size (H x W X D)</b>	47 x 37 x 28 cm	45 x 52 x 45 cm	86 x 55 x 45 cm	39 x 50 x 47 cm	47 x 51 x 49 cm
<b>Sorbency (pack)</b>	35 - 40 litres	70 - 80 litres	140 - 160 litres	42 - 48 litres	68 - 76 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain



- Outer Casing:** 100% polypropylene spun-bonded  
Tensile strength (mean): 400N (200mm strip/EN ISO 10319)  
UV resistant
- Filler:** Polypropylene and other fibres
- Fitted With:** Polypropylene thread tails for joining
- Pack Type:** Bag

**Compatibility:** Water-repellency exceeds requirements of BS 7959-2:2000.  
May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc.  
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.

**Fire Resistance:** Good. (Physically flame-retardant)  
Incinerable to zero ash.

**Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.

**Safety Data:** Refer to our Safety Data Sheet.  
This product is non-toxic to users and to aquatic life.  
Further technical advice is available if required.

**Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 10/12/2024