



Product Technical Specification Ultra-Flood Stopper® Bag

Product Summary

The Ultra-Flood Stopper® Bag is a revolutionary water barrier or sandless sandbag providing protection against floods, water heater leaks, broken pipes, overflowing toilets and other liquid emergencies.

Benefits

- Easy to use and transport •
- Sturdy construction passes multiple drop tests from 1 metre
- Quick acting the bag fills to capacity in 2.5 3.5 minutes, ready to prevent floods and leakage from causing damage
- Engineered consistency designed and built to maintain a ٠ consistent shape throughout the bag. The Ultra-Flood stoppers use an ingenious and patent pending method for assuring the complete distribution of water-absorbing polymer granules, when activated
- Fills to approximately 102mm height/13.6kg
- Safe, non-toxic, and can be disposed of at local landfill, subject to local rules.

Note: All weights, dimensions, and other figures quoted are approximate.

	0424/AB/15
Product Colour	Dark grey
Pack Quantity	15
Pack Weight	6.8kg
Size	305 mm x 610 mm x 6 mm
Weight - Dry	Approx. 0.27kg
Weight – Activated	Approx. 13.6 kg





Fabric:	Polypropylene with filler and treatment 70 GSM weight
Polymer:	Super Absorbent Polymer (SAP) – Proprietary Formula
Product Use:	Easy-to-use Ultra-Flood Stoppers [®] can be activated with fresh water in minutes. Use of a small, portable/ expandable pool (not included) that is filled with water is recommended. Drop Flood Stoppers into the water to allow the polymer to absorb and swell. Allow approximately 2.5 - 5 minutes to activate the units to 90% of capacity and remove the filled bags/tubes for placement. Add another batch of bags/tubes and continue until the needed supply for the application has been activated and placed into use.
	Ultra-Flood Stoppers® will usually work for a "season" (2-4 months or more) before they should be replaced and properly disposed of. They will lose weight and size in between usage as the retained water evaporates. Ultra-Flood Stoppers® can be recharged with additional fresh water prior to its next use.

Do not use for saltwater applications.

Email: sales@darcy.co.uk Call: 0800 0370 899

> darcy.co.uk DP-DS-10, Rev 2, 2025-03-07



