

SPECIFICATION FOR POLY OVER DRUMS



	1850/30	1849	1850
Height	765.3 mm	920.8 mm	1047.8 mm
Top outside dia.	581.2 mm	736.6 mm	819.2 mm
Weight	7.5 kg	20 kg	23.5 kg
Sump Capacity	113.5 litres	246 litres	359 litres
For use with	60 litre drum	120 litre drum	205 litre drum
Colour	Yellow	Yellow	Yellow
UN Marking	1H2/X100/S USA/+AA8744	1H2/X228/S USA/M5904	1H2/X345/S USA/M5904

Materials: Polyethylene

Description: Designed for the transportation of non-leaking drums that contain hazardous materials.
Single trip salvage drum – lid closure for transportation can only be performed once.
Excellent chemical resistance and corrosion resistant.
Extremely robust and durable.
Screw top closure.
UN approved – X rating packaging group 1
Certified for use as DOT Salvage Drums, 49 CFR 173.3 (c)

Manufacturing: 5 year guarantee against manufacturing defects.

Safety Data: Has been approved for solids only: use a loose absorbent to absorb any liquid before sealing.
Further technical advice is available if required.

Note: All weights, dimensions, and other figures quoted are approximate.

Revision Date: 19/08/2025