



## Ultra-Drain Guard

### Product Summary



	0119/DG/02/U	0119/DG/06/U	0119/DG
<b>Size (Unit)</b>	122 x 91 x 46 cm	122 x 91 x 46 cm	122 x 91 x 46 cm
<b>Colour</b>	Black	Black	Black
<b>Pack Quantity</b>	2	6	10
<b>Pack Wt (gross)</b>	1 kg	3 kg	5 kg
<b>Oil Capacity (Unit)</b>	< 3.5 litres	< 3.5 litres	< 3.5 litres
<b>Sediment Capacity (Unit)</b>	< 18 kg	< 18 kg	< 18 kg

- Composition:** Specially designed nonwoven polypropylene geotextile sewn by a double needle machine, using a high strength nylon thread.
- Flow rate:** Approx. 400 litres per minute (through material).
- Instructions for use:** Remove the drain cover.  
Clean dirt and debris from grating ledge and place the Drain Guard into the drain opening.  
Reinstall the drain cover. Drain Guard skirt must be secured (pinched) between drain cover and ledge.  
Cut the excess fabric off with a blade or knife if desired.  
Ultra-Drain Guard filters are designed to be used for 3 to 6 months under normal conditions. Where heavy contamination is present the unit will have a reduced life expectancy. When the unit has collected about 15cm of sediment, it is recommended that it be replaced. The unit should also be replaced if free oil can be seen floating and is not being absorbed. The Ultra-Drain Guards should be inspected on a regular basis.
- Compatibility:** May be safely used with all aqueous solutions and liquids immiscible.
- Fire Resistance:** None.
- Disposal:** In accordance with local and national regulations, taking into account the classification of the liquid absorbed.
- Safety Data:** Further technical advice is available, if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Email: [sales@darcy.co.uk](mailto:sales@darcy.co.uk)

Call: 0800 0370 899